Mackworth M-Series Floor Lifts





The Mackworth floor lifts are designed and manufactured using high quality components and construction to provide years of reliable service.

The M-Series floor lifts boast an impressive 350lb or 400lb (160 or 180kg) lifting capacity, a leg opening angle of 16 degrees or 43.31" (110cm) and market leading Linak® actuators and motors.

With its manually or electrically operated leg opening, the M-Series floor lift allows easy access to wider riser reclining chairs, large wheelchairs or even tight bed spaces. The product can be easily and compactly stored when not in use and has the ability to be folded on its end utilising small spaces fully.

Made from the finest steel, this amazing lifting technology is manufactured using the very best welding and laser guided cutting procedures.

Benefits

- Suitable for a wide range of environments with a safe working load of 350lb or 400lb (160 or 180kg)
- Strong, steel, powder coated frame, combining high lifting strength with economy
- High quality castors for ease of movement while under load
- Optional foldable, locking frame allows flat storage for optimised space management
- Wide leg opening facility for ease of approach to wide seating systems and riser recliners

Mackworth M-Series Floor Lifts

Technical specifications

Model	M350	M400
User weight limit (max rated load)	350lb (160kg)	400lb (180kg)
Frame construction material	Steel	Steel
Total weight (unboxed)	86lb (39kg)	86lb (39kg)
Lifting range (floor to carry bar center)	13.2-65" (335-1650mm)	12.8-70.1" (325-1780mm)
Leg opening range (internal)	20.28-39" (515-990mm)	20.1-37.4" (510-950mm)
Leg opening range (external)	26-45.1" (660-1145mm)	26.8-42.7" (680-1085mm)
Front castors	4" (100mm)	4" (100mm)
Rear braked castors	4" (100mm)	4" (100mm)
Hand Control	Linak®	Linak®
Actuator power	1800lbf (8,000N)	2250lbf (10,000N)

Features

- Models available with a safe working load of 350lb or 400lb
- Powder coated steel frame with high quality castors
- Foldable, locking frame option
- Manual or optional powered leg opening
- Linak® control and acuator



